



# 200 ACRYLIC TEXTURE BINDER ADDITIVE

## DESCRIPTION

**Anvil #200 Vinyl - Acrylic Binder Additive** is a clear vinyl - acrylic latex resin product formulated to improve the durability and adhesive properties of powdered wall & ceiling spray texture products. Also may be used as an additive to concrete or joint compound mixes to improve durability of the mixture. Use Anvil #200 full strength in place of water in the mix of textures, powdered joint compound or concrete.

## SURFACE PREPARATION

Follow manufactures directions for proper surface preparation before spraying

## THINNING

Normally none required

## APPLICATION

Follow manufactures directions for proper application techniques.

## LIMITATION OF LIABILITY

This product is manufactured to rigid control specifications. It is impossible to control the use and application. Therefore, the manufacturers sole liability is limited to replacing quantities of product proven to be defective. The manufacturer disclaims any liability for the cost of labor to repaint or any other use of the product.

## TECHNICAL DATA

**RESIN:** Vinyl - Acrylic Latex

**COLOR:** Milky (wet) - Clear (dry)

**GLOSS:** Low Sheen

**SOLID CONTENT:** BY WEIGHT - 56%  
BY VOLUME - 52%

**PIGMENT BY WEIGHT:** 0%

**VEHICLE BY WEIGHT:** 100%

**VISCOSITY:** Water like

**WEIGHT PER GALLON:** 9.1 lbs.

**FLASH POINT:** None

**DRYING TIME:** 70° F. & 50% Relative Humidity  
dependent on thickness of application.  
Touch - 1 to 6 hours

Do not apply at temperature below 50° F. Drying and cure times are influenced by ambient temperature and relative humidity.

**CLEANUP:** Water

**TINTING:** Not applicable

**VOC:** 11 grams/liter

**AVAILABLE IN 5 GALLON PAIL ONLY**

Revised 6-09 Supersedes all prior publications  
GRO

WARNING! WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.

Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! IRRITANT! HARMFUL IF SWALLOWED. IF TINTED, CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST.

WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID; if you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.