

ULTRASEAL COMMERCIAL SILICONIZED ACRYLIC CLEAR SEALER



1360

AVAILABLE SIZES
1 GALLON CAN
5 GALLON PAIL

RESIN: Silicone Acrylic
co-polymer

COLOR: Clear

SOLIDS BY WEIGHT: 25.0%

SOLIDS BY VOLUME: 31.15%

VISCOSITY: 65KU@75F

WEIGHT PER GALLON:
9.90 lbs.

FLASH POINT: 95F

RECOMMENDED COVERAGE:
300 to 500 sq. ft. per gallon, per
coat, depending on the type of
surface and porosity.

DRYING TIME@70F&50%RH:

To touch: 1/2 hour

To recoat: 3 to 4 hours

Foot traffic: 5 hours

Vehicle traffic: 72 hours

Drying times are influenced by
ambient temperature and relative
humidity.

CLEANUP: Xylene or Toluol

USES, FEATURES & BENEFITS

Anvil UltraSeal Commercial Siliconized Acrylic Floor Sealer is specially formulated with a modified siliconized acrylic co-polymer for use on unpainted concrete surfaces and provides excellent penetration and durability. It provides a clear semi-gloss protective topcoat on fully cured exterior unpainted concrete patios, decks, sidewalks, driveways and other exterior applications. (For interior surfaces, use Anvil UltraSeal Commercial Urethane/Acrylic Floor Sealer #1340). Also ideal for properly prepared vertical surfaces such as stucco, stone, brick, exposed aggregate concrete, textured concrete and other masonry surfaces. Used as a clear coat sealer on concrete and over most fully cured exterior concrete surfaces. Do not use on brick pavers, stamped concrete, epoxy or polyurethane coatings. Brush, roller or spray in both horizontal and vertical applications can be successfully achieved with UltraSeal #1360.

DIRECTIONS FOR USE AND SURFACE PREPARATION

Remove all dirt, efflorescence, grease, oil, waxes, acid residue and other foreign material that would interfere with the adhesion of the sealer. Uncoated smooth steel troweled concrete floors (floors with no porosity) must be totally cured, etched, neutralized, rinsed and cleaned for proper adhesion and durability of the sealer. A properly prepared surface will have the feel of 120 grit sandpaper. Porous vertical surfaces such as standard CMU, Tilt-up Construction, Split faced Block, and exposed aggregate generally do not require etching.

ULTRASEAL COMMERCIAL URETHANE/ACRYLIC FLOOR SEALER APPLICATION

Hand stir product thoroughly before application. Should be applied in thin multiple coats by brush (do not use a nylon brush), roller or spray. Avoid heavy application resulting in runs, ponding or puddling. Allow 3-4 hours drying time between coats. If relative humidity is high (> 80 percent), allow an extra period of drying time between coats. Two thin coats are recommended depending on the surface being coated and the gloss desired. Some surfaces such as inclined driveways, garages, patios, steps etc., may require a slip resistant additive for safety. Add Anvil #9102 Skid Resistant Additive to the final coat of UltraSeal. This product should not be used in place of a nonskid finish. Coverage is approximately 300 to 500 square feet per gallon, per coat, depending on the type of surface and porosity. Do not dilute or apply if the threat of rain is imminent or if the air/surface temperature is expected to be below 50 degrees F within the first 24 hours of application. Allow 3 days (72 hours) for a full cure before allowing vehicle traffic on the sealer.

CLEANUP

Brushes, roller covers should be properly discarded after use. Spray equipment can be cleaned with xylene or toluol. Dried sealer will be difficult to remove from any surface.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

DANGER! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

DANGER! FLAMMABLE LIQUID AND VAPOR HARMFUL OR FATAL IF SWALLOWED. ASPIRATION HAZARD. EXTERIOR USE ONLY. CAN ENTER LUNGS AND CAUSE DAMAGE. HARMFUL IF INHALED. MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS, INCLUDING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATIONS. OVEREXPOSURE MAY CAUSE BLOOD, LIVER, KIDNEY DAMAGE. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.

NOTICE: this product contains solvents. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm. For emergency information call (800) 545-2643.

For additional safety information, refer to the Material Safety Data Sheet for this product. Keep away from heat, sparks and flame. Do not smoke. Vapors may ignite. Extinguish all flames, burners, stoves, heaters and pilot lights and disconnect all electrical motors and appliances before use and until all vapors are gone. Prevent build-up of vapors by cross-ventilation. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use.

FIRST AID: In case of skin contact, wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin, then wash again with soap and water. Repeated applications may be needed. Remove contaminated clothing. For eye contact, flush immediately with large amounts of water, for at least 15 minutes. Obtain emergency medical treatment. If swallowed, obtain medical treatment immediately. If inhalation causes physical discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs, get medical help.

KEEP FROM FREEZING

EXTERIOR USE ONLY

VOC 598.0 grams/liter

revised 12-08 Supersedes all prior publications GRO



SILICONIZED ACRYLIC RESIN

SEMI GLOSS CLEAR SEALER

NON-YELLOWING

HARD, IMPACT RESISTANT

HIGH ABRASION RESISTANT

ALKALI RESISTANT

PENETRATES THE SURFACE

RESIST PEELING

LONG LASTING

EXTERIOR USE ONLY