



# 1400 STOP THE DRIP ACRYLIC SEALER

## DESCRIPTION

A solvent based clear acrylic sealer. Easy to apply, durable, weather tested, resists salt air oxidation and fungus.

## USES

Apply to the underside of the carport or cabana roof to stop dripping on cars or furniture. 1400 Stop the Drip Acrylic Sealer can be used on any metal surface that must take the punishment of damp weather, hot sun, and harsh element. It also acts as an excellent water repellent and rejuvenates old skylight surfaces.

## SURFACE PREPARATION

Surface to be painted must be clean and dry. Remove all dirt, excess chalky residue, oils, grease, mildew or other surface contaminants. Clean with a heavy duty cleaner such as Spic and Span. Make sure surface is completely dry before application.

## APPLICATION

Use brush, roller (fine nap-solvent resistant) or spray to apply. Best results are obtained when using airless spray equipment. Use in well lighted and ventilated area.

**COMBUSTABLE** Keep away from heat and open flame.

## LIMITATION OF LIABILITY

This product is manufactured to rigid control specifications. It is impossible to control the use and application. Therefore, the manufacturers sole liability is limited to replacing quantities of product proven to be defective. The manufacturer disclaims any liability for the cost of labor to repaint or any other use of the product.

Page 1 of 2

## TECHNICAL DATA

**PRODUCT NUMBER:** 1400

**RESIN:** Solvent Acrylic

**COLOR:** Clear

**GLOSS:** Semi-gloss

**SOLID CONTENT:**

BY WEIGHT: 22.6%

BY VOLUME: 15.9%

## RECOMMENDED COVERAGE:

200—400 Sq.Ft./gal. per coat, depending on the type of surface and porosity, at recommended dry film thickness 1 mil.

**% PIGMENT BY WEIGHT:** 0

**% VEHICLE BY WEIGHT:** 100

**VISCOSITY:** Water like

**WEIGHT PER GALLON:** 7.8 lbs

**FLASH POINT:** 81 F

**DRYING TIME** 70 F 50% R.H

Touch - 1/4 to 1/2 hour

Recoat - 1/2 to 1 hour

Recoat by Brush - 12 hours

Full Cure - 12 hours

Do not apply when rain, cold or night fall is imminent. If humidity is close to 100%, or in the event of heavy fog, some drips may occur. Do not apply WAX over this coating - it will kill the effect.

**THINNER/CLEANUP:** Xylene

**TINTING:** Not applicable

**VOC:** 730.4 grams/liter

**AVAILABLE IN QTS. 1 & 5 GALLON CANS**

Revised 1-09 Supersedes all prior publications GRO

**WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE. ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED, WHEN TINTED, CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.**

To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID;** if you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**