



1404 TILE & SHINGLE GLAZE CLEAR

DESCRIPTION

A clear acrylic latex emulsion product. Non-flammable, non irritating vapors - water based emulsion that is easy to apply.

USES

Designed for use as a glaze coat on concrete tile, shingle roofs and skylights.

SURFACE PREPARATION

Remove all loose dirt, paint flakes, oils, and other surface contaminants. Pressure clean tiles and apply a mildewcide to the entire area. Allow to dry thoroughly before application.

APPLICATION

Use brush, roller or spray to apply. Best results are obtained when using airless spray equipment. 1404 is milky in appearance while wet, and clear when completely dry. Use two light coats, 15 to 20 minutes apart rather than a single heavy flood coat.

THINNING

Normally none required.

LIMITATION OF LIABILITY

This product is manufactured to rigid control specifications. It is impossible to control the use and application. Therefore, the manufacturer's sole liability is limited to replacing quantities of product proven to be defective. The manufacturer disclaims any liability for the cost of labor to repaint or any other use of the product.

Page 1 of 2

TECHNICAL DATA

PRODUCT NUMBER: 1404

RESIN: Acrylic Latex

COLOR: Clear (dry)

GLOSS: Semi-gloss

SOLID CONTENT:

BY WEIGHT: 30%

BY VOLUME: 28%

RECOMMENDED COVERAGE:

250 Sq.Ft./gallon dry film thickness 1 mil.

% PIGMENT BY WEIGHT: 0

% VEHICLE BY WEIGHT: 100

VISCOSITY: Water like

WEIGHT PER GALLON: 8.5 lbs

FLASH POINT: None

DRYING TIME: 70 F 50% R.H.

Touch - 1/4 hour

Recoat - 1/4 to 1/2 hour

Full cure - 1 to 2 hours

Do not apply when ambient temp. is below 50 F or at or near 100% humidity, cold or darkness is imminent.

THINNER/CLEANUP: Water

TINTING: Not applicable

VOC: 221.1 grams/liter

AVAILABLE IN 1 & 5 GALLON PAILS

Revised 1-09 Supersedes all prior publications GRO

WARNING! WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. WARNING! IRRITANT! IRRITANT! HARMFUL IF SWALLOWED. IF TINTED, CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. FIRST AID; if you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.