



CHATTAHOOCHEE STONE SEALER & GLAZE COAT



1950

AVAILABLE SIZES
1 GALLON CAN
5 GALLON PAIL

RESIN: Oil Modified Urethane

COLOR: Amber Tint Clear

SOLIDS BY WEIGHT: 31.0%

VISCOSITY: 58KU@75F

WEIGHT PER GALLON:
7.02 lbs.

FLASH POINT: 105F

RECOMMENDED COVERAGE:
100 sq. ft. per gallon, per
coat, depending on the size of
stone and porosity.

DRYING TIME@70F&50%RH:
To touch: 2 hours
To recoat: within 8 hours
Recoat within 8 hours or after 24
hours of applicaion of first coat.
Drying times are influenced by
ambient temperature and relative
humidity.

CLEANUP: Mineral Spirits

USES, FEATURES & BENEFITS

Anvil Chattanooga Stone Sealer & Glaze Coat is formulated with an Oil Modified Urethane Resin for added toughness and abrasion resistance. It delivers a warm hue which helps restore the original look of Chattanooga stone surfaces. Ideal for sealing and glaze coating of both mortar and epoxy set stone. The sealer is resistant to pool chemicals, ultra violet light and most household detergents. Packaged to be used 'as is' with no thinning needed. Anvil's Chattanooga Stone Sealer & Glaze Coat helps prolong the life of Chattanooga stone decks and walkways.

DIRECTIONS FOR USE AND SURFACE PREPARATION

Remove all dirt, efflorescence, grease, oil, waxes, mildew, acid residue and other foreign material that would interfere with the adhesion of the sealer. High pressure water wash is recommended. A mixture of 1 part household bleach and 3 parts water is recommended for mold and mildew removal, rinse with clean water. Avoid the use of household detergents that could leave a hard to remove soap residue. Allow the surface to dry completely after washing or rain for at least 24 hours.

CHATTANOOCHEE SEALER & GLAZE APPLICATION

Hand stir product thoroughly before application. Should be applied in thin multiple coats by brush (do not use a nylon brush), roller or spray. Avoid heavy application resulting in runs, ponding or puddling. Recoat within 8 hours of first coat application. If the 8 hour recoat interval has been exceeded, recoat after 24 hours. If relative humidity is high (> 80 percent), allow an extra period of drying time between coats. Two thin coats are recommended depending on the surface being coated. Some surfaces such as inclined driveways, garages, patios, steps etc., may require a slip resistant additive for safety. Add Anvil #9102 Skid Resistant Additive to the final coat of Sealer & Glaze. This product should not be used in place of a nonskid finish. Coverage is approximately 100 square feet per gallon, per coat, depending on the type of surface and porosity. Do not dilute or apply if the threat of rain is imminent or if the air/surface temperature is expected to be below 50 degrees F within the first 24 hours of application. Allow 3 days (72 hours) for a full cure before allowing heavy traffic on the sealer.

CLEANUP

Brushes, roller covers should be properly discarded after use. Spray equipment can be cleaned with mineral spirits. Dried sealer will be difficult to remove from any surface.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE. ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

DANGER! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! COMBUSTIBLE LIQUID AND VAPOR HARMFUL OR FATAL IF SWALLOWED. ASPIRATION HAZARD. EXTERIOR USE ONLY. CAN ENTER LUNGS AND CAUSE DAMAGE. HARMFUL IF INHALED. MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS, INCLUDING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATIONS. OVEREXPOSURE MAY CAUSE BLOOD, LIVER, KIDNEY DAMAGE. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.
NOTICE: this product contains solvents. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm. For emergency information call (800) 545-2643.

For additional safety information, refer to the Material Safety Data Sheet for this product. Keep away from heat, sparks and flame. Do not smoke. Vapors may ignite. Extinguish all flames, burners, stoves, heaters and pilot lights and disconnect all electrical motors and appliances before use and until all vapors are gone. Prevent build-up of vapors by cross-ventilation. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use.
FIRST AID: In case of skin contact, wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin, then wash again with soap and water. Repeated applications may be needed. Remove contaminated clothing. For eye contact, flush immediately with large amounts of water, for at least 15 minutes. Obtain emergency medical treatment. If swallowed, obtain medical treatment immediately. If inhalation causes physical discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs, get medical help.
KEEP FROM FREEZING

DO NOT THIN EXTERIOR USE ONLY

VOC 580 grams/liter

revised 11-2011 Supersedes all prior publications GRO



OIL MODIFIED URETHANE RESIN

SEMI GLOSS SEALER

HARD, IMPACT RESISTANT

HIGH ABRASION RESISTANT

AMBER TINT CLEAR

RENEWS RICH LOOK OF STONE

RESIST PEELING

LONG LASTING

EXTERIOR USE ONLY

CLEANUP: MINERAL SPIRITS