



# PAVER SEALER

## 100% ACRYLIC



RESIN: acrylic solution

COLOR: clear

SOLIDS BY WEIGHT: 24.0%

SOLIDS BY VOLUME: 19.83%

VISCOSITY: 20sec #2-ZAHN  
@75F

WEIGHT PER GALLON:  
7.66 lbs

FLASH POINT: 108F

RECOMMENDED COVERAGE:  
125-300 sq. feet depending on the  
type of paver and surface  
porosity.

DRYING TIME@75F&50%RH:  
To touch: 1/2 to 1 hour  
To recoat: 2 hours  
Vehicle traffic: 3 days

CLEAN-UP: xylene

### 1955

AVAILABLE SIZES

1 GALLON CANS

5 GALLON PAILS

## USES, FEATURES & BENEFITS

**Anvil #1955 100% Acrylic Paver Sealer** is a solvent based, non-yellowing clear coating for glazing and sealing bare and colored brick and concrete pavers. **Anvil 100% Acrylic Paver Sealer** delivers a medium gloss when applied to a properly prepared surface and is highly resistant to the effects of hot automobile tires. It is formulated for use on exterior unsealed concrete pavers and concrete surfaces such as patios, walkways, decks, decks and sidewalks. Also, **Anvil #1955 100% Acrylic Paver Sealer** is formulated to be resistant to mild automotive chemicals, oil, grease and gasoline. Its' durable acrylic formula also resists fading, scuffing, cracking, peeling and blistering.

### DIRECTIONS FOR USE AND SURFACE PREPARATION

Proper preparation will insure maximum adhesion, durability, and uniform coloration, ASTM D4258-83 Specification. The surface must be clean and free of all wax, grease, oil, dirt, acid, mildew, release agents and all other surface contaminants. Failure to remove grease, oil, soap or other contamination will interfere with adhesion of the Paver Sealer. New pavers should be sweep clean to remove sand or dirt. Older pavers must be clean. To clean surface, scrub with a solution of 1/2 cup of TSP (Trisodium Phosphate) per gallon of clean hot water. Rinse thoroughly with a power washer. Previously sealed pavers should be examined closely to be sure that the previously sealed pavers will accept the new application. Anvil #1955 100% Acrylic Paver Sealer will adhere to most sealers that are old and weathered away, but will not adhere to silicate or siloxane type sealers. Unpainted concrete surfaces should be mechanically abraded or acid etched before sealing, ASTM D4260 Specification. Use 1 part muriatic acid to 3 parts clean water. Apply acid solution with a plastic sprinkling can and allow to stand for 15 minutes. Power wash etched area thoroughly and NEUTRALIZE WITH A SOLUTION OF 1 PART HOUSEHOLD AMMONIA AND 20 PARTS CLEAN WATER. Rinse area thoroughly and allow drying COMPLETELY before sealing. A properly etched surface will have the feel of 120 grit sandpaper.

Extremely hard, glossy or alkaline concrete may require stronger acid solutions or repeated etching. Concrete should be at least 45 days old to reduce the possibility of the occurrence of efflorescence. Do not apply to concrete where hydrostatic pressure is present or over 3 lbs. of moisture per 1000 sq. ft. ASTM F1869-04. Not intended for use over wood or areas of standing water. Check for a high pH, ASTM D4262 specification.

### APPLICATION

Hand stir product thoroughly before application. Apply in one thin coat by brush, roller, fan tip pump sprayer or airless sprayer. Avoid heavy application resulting in runs, ponding, flood coating or puddling. Allow two hours drying time, if relative humidity is high (> 80 %), allow an extra period of drying time. One thin coat is recommended, do not apply multiple coats for danger of turning milky white by moisture contact. Some surfaces such as inclined driveways, garages, patios, steps etc. may require a slip resistant additive for safety. Add Anvil #9102 Talon Grip Slip Resistant Additive to the coat. This product should not be used in place of a non-skid finish. Coverage is approximately 125 sq. ft. per coat over coarse concrete pavers and 300 sq. ft. per gallon, per coat, over smooth concrete. Do not dilute. Do not apply if the threat of rain is imminent or if the air/surface temperature is expected to be below 50°F within the first 24 hours of application. Do not apply in extreme heat of day or in direct hot sunlight. Allow 3 days (72 hours) before allowing vehicle traffic on the coating. Full cure in 21 days. We

recommend that a parked car stand on cardboard until full cure.

### CLEAN-UP

Clean immediately with Xylene/Toluene

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE. ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**CONTENTS ARE FLAMMABLE.** Vapors may cause flash fires. Keep away from heat, sparks and open flame during use and until all vapors are gone. Keep area ventilated – do not smoke – extinguish all flames, pilot lights, and heaters – turn off stoves, electric tools and appliances, and any other sources of ignition. CONTAINS TOLUENE & XYLENE. VAPOR HARMFUL. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (IOSH/MSHA TC23C or equivalent) or leave area. AVOID CONTACT WITH EYES AND SKIN. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. IF SWALLOWED, DO NOT INDUCE VOMITING. Get medical attention immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents, which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. USE WITH ADEQUATE VENTILATION. USE PROTECTIVE CLOTHING TO AVOID CONTACT WITH SKIN AND EYES. KEEP AWAY FROM CHILDREN. KEEP FROM FREEZING.**

VOC: 592.6 grams/liter



100% ACRYLIC

NON-YELLOWING

MEDIUM GLOSS

APPLY ONE THIN COAT ONLY

PAVERS OR CONCRETE

EXTERIOR USE ONLY

RESISTANT TO MILD AUTO  
CHEMICALS

USE ON UN-SEALED PAVERS

XYLENE/TOLUENE CLEAN UP