



ULTRA TEX

SUPER HARD TEXTURE SYSTEM

AGGREGATED COARSE TEXTURE

part 2 of 2



RESIN: 100% Acrylic modified for superior durability & scrubability
COLOR: custom mixed TB
 up to 8 oz universal colorant per gallon
GLOSS: flat
TEXTURE: COARSE
SOLIDS BY WEIGHT:70.2%
SOLIDS BY VOLUME: 50.3%
VISCOSITY: 135+ KU@75F
WEIGHT PER GALLON: 13.6lbs
FLASH POINT: none
PERMEANCE:(ASTM D-1653) 30+
MILDEW GROWTH: (MIL SPEC 810E) 0%
FIRE&SMOKE:(ASTM E84) non-combustible Class A
SCRUBBAABILITY: (ASTM D-2486) 4,000+
PENCIL HARDNESS: (ASTM D-3363) 4H
RECOMMENDED COVERAGE: 125sq. feet per gallon @ 70% coverage
TOTAL SYSTEM DFT: 12-22 mils
DRYING TIME@75F&50%RH: To touch: 4-6 hours
 Full cure: 7 days
 Drying times are influenced by ambient temperature and relative humidity.
CLEAN-UP: soap & water

2220

AVAILABLE SIZES
5 GALLON PAILS

USES, FEATURES & BENEFITS

ULTRA TEX 2220 AGGREGATED COARSE TEXTURE FINISH is designed as texture choice to the two-coat Ultra Tex System that provides an ultra-tough, durable, breathable decorative commercial textured wall finish on interior walls. **ULTRA TEX 2220** is a acrylic breakthrough product that is pigment rich and contains no cement or plaster compounds.

ULTRA 2220 remains slightly flexible when cured thereby making it extremely resistant to cracking and chipping under the most demanding commercial/hospitality environment. **ULTRA TEX 2220** color choices for the texture finish is available in a wide range of pastel to medium colors from most Color Systems or can be custom matched to project specifications. **ULTRA TEX System** is highly permeable and is treated with fungicide to resist mildew growth on the product film.

ULTRA TEX 2210 AGGREGATED FINE TEXTURE FINISH is designed as the Texture coat Over **ULTRA TEX 2205 BASE COLOR COAT** and to be texture pump applied to provide an unlimited variety of surface profiles and texture effects. **ULTRA TEX System** is a texturizing process is used on interior surfaces of drywall or masonry construction as a replacement for vinyl wallpaper. The finish produced by this product system is excellent for walls in hotels, motels, offices, apartments, restaurants, health care and other high-traffic or commercial buildings.

DIRECTIONS FOR USE AND SURFACE PREPARATION

Surface must be previously coated with **ULTRA TEX 2205 BASE COLOR COAT**. Wall surfaces should be dry, free of dust, grime or other contaminants that could interfere with the bonding characteristics of **ULTRA TEX 2220 AGGREGATED COARSE TEXTURE FINISH**.

COVERAGE

As a Texture Coat coverage will vary according to surface porosity and equipment used. Average coverage is 125 square feet per gallon. A test application is recommended to determine actual coverage under specific job conditions.

APPLICATION

ULTRA TEX 2220 AGGREGATED COARSE TEXTURE is the second coat spray-designed Ultra Tex System. The Texture Coat can be applied by hopper gun or through a texture pump and gun at package consistency. Obtain “knock down” effect by smoothing the peaks with a stainless steel trowel. Drying time to the point of achieving desired “knock down effect” will vary due to temperature, humidity and other conditions at the time of application and is best determined by test applications. Texture coat can be troweled on with a stainless steel trowel. Always work to a wet edge. Varying orifice size, air pressure and knock down technique will have an effect on finish appearance. Experimentation and test application are recommended. Once a procedure has been determined to achieve the desired results all changes including applicator should be avoided until a different wall or natural breaking point has been reached.

COLOR

ULTRA TEX 2220 AGGREGATED COARSE TEXTURE is tintable at store level with most Color Systems in pastel to medium shades. Use 1-gallon color formula as a starting point in color matching. Up to 8 oz. of colorant per gallon.

MILDEW CONTROL

Controlling moisture is the key to controlling mildew. Without moisture, mold and mildew cannot absorb nutrients and grow, no matter how many spores are present. Traditional vinyl wallcoverings contribute to moisture by acting as a vapor barrier. **ULTRA TEX SYSTEM** is the ideal solution. **ULTRA TEX SYSTEM** “breathes” to allow moisture to escape. **ULTRA TEX 2220 AGGREGATED COARSE TEXTURE** is also fortified with mold and mildew growth inhibitors.

CLEANUP

Clean all equipment immediately after use with warm soapy water. Dried material will be extremely difficult to remove.

WARRANTY AVAILABLE

Limited 10-Year Product Performance Warranty

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE. ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a EPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED, WHEN TINTED, CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.

To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying.

If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID;** if you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.



SOLID COLOR THROUGHOUT

HIDES SURFACE IMPERFECTIONS

MILDEW AND MOLD RESISTANT

LIMITED 10 YEAR WARRANTY

EXTREMELY SCRUBBABLE AND DURABLE

EASY TO CLEAN AND RESISTS STAINING

COARSE AGGREGATED TEXTURE



VOC: 88.9 grams/liter

Revised 5-09 Supersedes all prior publications GRO