

'WET LOOK' SEALER SUPER CLEAR INTERIOR/EXTERIOR



2350

AVAILABLE SIZES
1 GALLON CANS
5 GALLON PAIL

RESIN: Acrylic, self-crosslinking

COLOR: Milky white, dries clear

GLOSS: High

SOLIDS BY WEIGHT: 28.9%

SOLIDS BY VOLUME: 27.2%

VOC: (as packaged) 195 g/l
(1.63 lbs./gal)

WEIGHT PER GALLON: 8.47 lbs.

FLASH POINT: None

RECOMMENDED COVERAGE:
200 to 400 sq. ft. per gallon, per
coat, depending on the type of
surface and porosity.

DRYING TIME: @70F&50%RH
To touch; 1/2 to 1 hour
To recoat; 4 hours
Foot traffic; 3 to 4 hours
Vehicle traffic; 72 hours
Drying times are influenced by
ambient temperature and relative
humidity.

CLEANUP: Water

VOC: 218.4 grams/liter

Revised 12 2008
Supersedes all prior publications GRO

USES, FEATURES & BENEFITS

Anvil #2350 'Wet Look' Sealer combines the extra durability and wet look to stained or uncoated concrete for both interior and exterior applications. Water reducible clear 'Wet Look' Sealer is non-yellowing and is low odor. Anvil #2350 'Wet Look' Sealer when applied to a properly prepared surface is highly resistant to the effects of hot automobile tires. Anvil #2350 'Wet Look' Sealer is formulated for use on surfaces such as driveways, garage floors, patios, walkways, sidewalks, decks, pavers, un-glazed tile, brick and stucco. Anvil #2350 'Wet Look' Sealer is milky white when applied, but dries to a natural super clear gloss finish. However, Anvil #2350 'Wet Look' Sealer is not intended for use over wood, metal, granite, terrazzo, marble surfaces or other natural stone products.

DIRECTIONS FOR USE AND SURFACE PREPARATION

Proper surface preparation will insure maximum adhesion and durability, ASTM D4258-83 Specification. The surface must be clean and free of all wax, grease, oil, dirt, acid, mildew, release agents and all other surface contaminants. Failure to remove grease, oil, soap or other contamination will interfere with adhesion of the 'Wet Look' Sealer. To clean surface, scrub with a solution of 1/2 cup of TSP (Trisodium Phosphate) per gallon of clean hot water. Rinse thoroughly with a power washer. Glossy painted surfaces must be dulled. Unpainted concrete surfaces should be mechanically abraded or acid etched before coating, ASTM D4260 Specification. Use 1 part muriatic acid to 3 parts clean water. Apply acid solution with a plastic sprinkling can and allow to stand for 15 minutes. Power wash etched area thoroughly and NEUTRALIZE WITH A SOLUTION OF 1 PART HOUSEHOLD AMMONIA AND 20 PARTS CLEAN WATER. Rinse area thoroughly and allow to dry COMPLETELY before sealing. A properly etched surface will have the feel of 120 grit sandpaper. Extremely hard, glossy or alkaline concrete may require stronger acid solutions or repeated etching. Concrete should be at least 45 days old to reduce the possibility of the occurrence of efflorescence. Do not apply to concrete where hydrostatic pressure is present or over 3 lbs. of moisture per 1000 sq. ft. ASTM F1869-04. Check for high pH, ASTM D4262 specification. Surface must be clean, dry, and free of loose or chalking paint and other surface contaminants.

APPLICATION

Hand stir product thoroughly before application. Sealer should be applied in thin multiple coats by brush, roller, pad or spray. Spray application should be back rolled for uniform film thickness. Avoid heavy application resulting in runs, ponding, flood-coating or puddling. Allow four hours drying time between coats. If relative humidity is high (>80%), allow an extra period of drying time between coats. Two thin coats are recommended depending on the surface being coated and the gloss desired. On pavers, do not exceed one thin coat. Some surfaces such as inclined driveways, garages, patios, steps, etc. may require a slip resistant additive for safety. Add Anvil #9102 Talon Grip Slip Resistant Additive to the final coat of 'Wet Look' Sealer. This product

should not be used in place of a nonskid finish. Coverage is approximately 200 to 400 square feet per gallon, per coat, depending on the type of surface and porosity. Do not dilute or apply if the threat of rain is imminent or if the air/surface temperature is expected to be below 50°F within the first 24 hours of application. Do not apply in extreme heat of day or in direct hot sunlight. Allow 3 days (72 hours) before allowing vehicle traffic on the stain. Full cure in 21 days. We recommend that a parked car stand on cardboard until full cure.

CLEAN-UP

Clean immediately with warm, soapy water.

WARNING! WARNING! If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. **WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! IRRITANT! HARMFUL IF SWALLOWED. IF TINTED, CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.

To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID;** if you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. **CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**



NON-FLAMMABLE

WATER REDUCIBLE ACRYLIC

LOW ODOR

SUPER CLEAR GLOSS WET LOOK

RESISTANT TO HOT AUTO TIRES

INTERIOR/EXTERIOR

USE ON STAINED OR UNCOATED CONCRETE

MULTIPLE COATS INCREASE GLOSS

