



# BLUE LIQUID MASKING 245



## 245

AVAILABLE SIZES  
1 QUART CANS  
1 GALLON CANS  
5 GALLON PAILS

RESIN: Acrylic co-polymer

COLOR: Transucent Blue

GLOSS: Not Applicable

SOLIDS BY WEIGHT: 42%

SOLIDS BY VOULUME: 42%

VISCOSITY: 110 KU

WEIGHT PER GAL.: 8.74lbs

FLASH POINT: None

RECOMMENDED COVERAGE  
80-120 Sq.Ft./Gal at a wet film  
thickness of 6 to 10 Mils.

DRYING TIME: 70F & 50%R.H  
Touch- 1/2 to 1 hour  
Recoat- 2 to 4 hours  
Full Cure- 24 hours

CLEAN-UP: Soap & Water

PACKAGING: Quart, Gallon &  
Five Gallon Pails

VOC: 95 grams/liter (.79 lbs/gal)

## USES, FEATURES & BENEFITS

Anvil #245 Blue Liquid Masking is formulated for use when painting and masking windows/doors and glass. It forms a tough, flexible protective coating that can be easily removed from glass after a few hours or stays flexible, pliable and strippable for up to 30 days. It is a primer for ready to paint wood as it is applied to the total surface of windows or doors. It adheres to wood and removes easily from glass, fiber-glass gel coats and glazed tile.

## SURFACE PREPARATION

All dust, dirt, soot, grease, calcium or salt film, fungus, mildew, algae or other contamination must be removed. Glass must be clean and free from contaminants. Surface must be clean and dry. Blue Liquid Masking adheres to wood, primed metal, aluminum and dulled painted surfaces. Do a test area first to check for adhesion, removal properties and compatibility of the finish coat.

## APPLICATION

Use brush, roller or spray to apply. Best results are obtained when using airless spray equipment. Two uniform coats of Blue Liquid Masking applied at 10 wet mils @ 160 sq. ft. per gallon will form a strippable film. Allow 1 to 2 hours dry time between coats. Expect 80 sq ft. per gallon for two coats. If priming bare wood windows and protecting glass, apply at 6 mils wet uniformly. Do not apply lacquers or top coats containing ketones or alcohol. **Caution:** Anvil Blue Liquid Masking will adhere to vinyl, aluminum, plastic, frosted glass and Plexiglass,

## REMOVAL

From window sashes use a dull blade and cut close to the sash and peel off from the glass. From fiber-glass gel coats remove by manual peeling away the coating or pressure washing.

## CLEAN-UP

Clean immediately with warm, soapy water.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** We a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARNING!** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protections; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN—DO NOT TAKE INTERNALLY.**

## LIMITATION OF LIABILITY

This product meets ANVIL's manufacturing specifications. It is impossible to control the use and application. Therefore, the manufacturers sole liability is limited to replacing quantities of product, upon proof of purchase, if this product does not meet these specifications. The manufacturer disclaims any liability for the cost of labor for removal or application of any product or any incidental or consequential damages.



Issued 08/08 GRO



TRANSLUCENT BLUE

PRIMES AND ADHERES TO  
WOOD AND METAL

EASILY REMOVED FROM GLASS

STAYS FLEXIBLE

PROTECTS GEL COATS

SPRAY, BRUSH, ROLL

SAVE TIME MASKING

SOAP/ WATER CLEANUP

INTERIOR OR EXTERIOR