

# HIGH HIDE BUILDERS SPEC INTERIOR/EXTERIOR



## 500 SATIN

### AVAILABLE SIZES

- 1 Gallon Cans
- 5 Gallon Pails

RESIN: Vinyl Acrylic  
COLOR: Tint Bases  
501 Pastel  
502 Medium  
503 Deep  
GLOSS: Satin  
SOLIDS BY WEIGHT: 40.8 %  
SOLIDS BY VOULUME:26.2 %

VISCOSITY: 92 KU@75F

VOC: (as packaged) 97.1 g/l  
(.811 lbs./gal) Complies with all  
Federal, State and Local VOC  
requirements.

WEIGHT P/ GALLON: 10.63 lbs

FLASH POINT: None  
RECOMMENDED COVERAGE:  
200 to 400 Sq. Ft. per Gallon, per  
coat, depending on the type of  
surface and porosity.

DRYING TIME:  
@70F 50% RH  
To touch; 1/2 to 1 hour  
To recoat; 1 to 2 hours  
Drying times are influenced by  
ambient temperature and relative  
humidity.

APPLICATION EQUIPMENT:  
Airless Spray  
CLEAN UP: Soap & Water

## USES, FEATURES & BENEFITS

Anvil High Hide Builders Spec products are specially formulated with durable Vinyl Acrylic Resins for use in residential, architectural and commercial applications on a diverse number of properly prepared substrates. It is low odor, water reducible and non-flammable. It provides a Satin finish with high hiding properties, achieved best buy airless spray application. Formulated for interior and exterior applications where the Professional Painting Contractor needs economy and ease of application with good wet and dry hide.

## DIRECTIONS FOR USE AND SURFACE PREPARATION

Surfaces must be completely dry and in sound condition. Surface should be clean and free from construction dust and dirt, grease, mill oils, rust, scale, chalky paint, efflorescence, organic growth, mildew or other foreign matter that would impair the adhesion performance of High Hide Builders Spec. Pressure washing, sandblasting, power tool cleaning, hand tool cleaning, scraping or wire brushing should be employed to remove peeling, chipping and cracking paint. All glossy surfaces should be sanded or deglossed. Feather sand rough edges of previously painted surface and spot prime bare areas. All unpainted substrates should be properly prepared and primed with the recommended primers. For new Gypsum Wallboard and Interior Plaster, allow all drywall joint compound and plaster thoroughly dry and prime with Anvil 235 AquaSeal or self-prime. Previously painted Wallboard or Plaster should be primed with 235 or self primed if the surfaces are in good condition. New Concrete and Masonry, prime alkaline substrate (pH range 8-10) with Anvil 1606 All Purpose Primer or Anvil 345 'Hot' Block Filler. Previously painted masonry should be primed with Anvil 230/1 Chalky Surface Conditioner or Anvil 1606 All Purpose Primer, surfaces in good condition can be self-primed. New Wood, Plywood, Ferrous Metal, Galvanized, Rusted or Aluminum should be primed with Anvil 1606 All Purpose Primer, if previously painted and in good condition self-prime.

## HIGH HIDE BUILDERS SPEC APPLICATION

Mix thoroughly and stir frequently while using to maintain consistency. Insure color uniformity, by inter-mixing product before use. Airless spray tip size should reflect equipment type and pressure, applicator technique and surface conditions. Generally a tip size between 0.015" and 0.021" are used. Application rate will be 200 to 400 sq. ft. per gallon, depending on the type of surface and porosity. Adjust pressure for constant and proper atomization. Work to maintain a wet edge and on porous surfaces, immediate 'back rolling' with wet roller is recommended to help reduce pin holing and to assist working the material into the pores. Curing and drying time will affect the performance of the product. Do not apply when air, surface or product temperatures are below 50 F or above 100 F. Surface temperature must be at least 5 F above the dew point. Plan ahead and avoid spraying when damp or threatening weather is expected.

Product must cure at least 8 hours before being subjected to moisture. Do not apply late in the day where dew or condensation may form before product begins to cure. During extremely hot weather, maintaining a wet edge may become difficult. Avoid application during the heat of the day. Allow High Hide Builders Spec to cure a minimum of 30 days before cleaning. Allow one to two hours cure time between coats.

## CLEAN UP

Clean all tools and equipment with warm soapy water immediately after use. Flush spray equipment thoroughly with clean water.

**WARNING!** If your scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear and NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead)

**WARNING! HARMFUL IF INHALED. MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS, INCLUDING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. HARMFUL IF SWALLOWED. MAY BE HARMFUL IF ABSORBED THROUGH SKIN. OVEREXPOSURE MAY CAUSE LIVER, KIDNEY DAMAGE. WHEN TINTED, CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. USE ONLY WITH ADEQUATED VENTILATION. KEEP OUT OF THE REACH OF CHILDREN. NOTICE: this product contains solvents.** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.** For emergency information call (800) 545-2643. For additional safety information, refer to the Material Safety Data Sheet for this product. If sanding is done, wear a dust mask to avoid breathing of sanding dust. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, leave the area. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use. **FIRST AID:** In case of skin contact, wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin, then wash again with soap and water. Repeated applications may be needed. Remove contaminated clothing. For eye contact, flush immediately with large amounts of water, for at least 15 minutes. **Obtain emergency medical treatment.** If swallowed, **obtain medical treatment immediately.** If inhalation causes physical discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs, get medical help. **KEEP FROM FREEZING**

VOC: 126.5 grams/liter



## Anvil Paints & Coatings

1255 Starkey Road  
Largo, Florida 33771  
FAX 727.535.1413  
1.800.822.6776

[anvilpaints.com](http://anvilpaints.com)



INTERIOR/EXTERIOR

LOW ODOR

WATER REDUCIBLE ACRYLIC

SATIN FINISH

NON-FLAMMABLE

HIGH HIDING

GOOD WET AND DRY HIDE

AIRLESS SPRAY APPLICATION

RESISTS DIRT PICK UP

GOOD WASHABILITY