



ANVIL PAINTS & COATINGS, INC.
1255 STARKEY ROAD
LARGO, FL 33771

MATERIAL SAFETY DATA SHEET

EMERGENCY TELEPHONE NUMBERS:

800-424-9300 (CHEMTREC)
 727-535-1411

REVIEW/UPDATE: JAN 2009

=====

SECTION ONE - PRODUCT DESCRIPTION

=====

NAME: TEXTURE WALL SYSTEM - BASE COAT COLOR COAT
CHEMICAL DESCRIPTION: Pigmented Acrylic Emulsion
FORMULA: #2205

=====

SECTION TWO - HAZARDOUS INGREDIENTS

=====

CHEMICAL	PERCENT	CAS NO.	TLV	PERMISSIBLE EXPOSURE LEVEL	CARCINOGEN Y/N	NOTE
Ethylene Glycol	1.19	107-21-1	NE	NE	N	
Calcium Carbonate	16.16	1317-65-3	10 mg/m ³	15 mg/m ³	N	
Titanium Dioxide	9.24	13462-67-7	10 mg/m ³	10 mg/m ³	N	
Mica	2.31	12001-26-2	3 mg/m ³	3 mg/m ³	N	
Aluminum Silicate	3.46	1332-58-7	N/A	N/A	N	
Acrylic Copolymer	11.1	supp. conf.	50	not est.	N	
Texanol	1.09	25265-77-4	NE	NE	N	

=====

SECTION THREE - PHYSICAL DATA

=====

APPEARANCE: White **ODOR:** Nondescript, **BOILING POINT:** 100°C/212°F,
VAPOR PRESSURE: (mm of Hg.): 17@20°C/68°F, **VAPOR DENSITY (Air = 1):** >1,
SPECIFIC GRAVITY (Water = 1): 1.30, **VOLATILE BY WEIGHT:** 56.44%
SOLUBILITY IN WATER: Dilutable, **EVAPORATION RATE (Water = 1):** >1

=====

SECTION FOUR - FIRE AND EXPLOSION DATA

=====

FLASH POINT (°F / °C) [Closed Cup]: Non Combustible
FLAMMABLE LIMIT: - LEL N/A - UEL N/A
EXTINGUISHER MEDIA: N/A
SPECIAL FIRE FIGHTING PROCEDURES: N/A
UNUSUAL FIRE AND EXPLOSION HAZARDS: Polymer film will burn. Material can splatter above 100°C/212°F.

=====

SECTION FIVE - HEALTH HAZARD DATA

=====

THRESHOLD LIMIT VALUE: See section two
EFFECTS OF OVEREXPOSURE:

- Inhalation:** Vapor or mist can cause headache, nausea, irritation to the nose, throat and lungs.
- Skin Contact:** Irritating upon repeated and prolonged contact.
- Eye Contact:** Slightly irritating.

EMERGENCY & FIRST AID PROCEDURES:

- Inhalation:** Move subject to fresh air.
- Eye/skin Contact:** Flush eyes with large amounts of water for at least 15 minutes - see a physician if irritation persists. Wash Affected skin area with soap and water.

