



ANVIL PAINTS & COATINGS, INC.
1255 STARKEY ROAD
LARGO, FL 33771

MATERIAL SAFETY DATA SHEET

EMERGENCY TELEPHONE NUMBERS: 800-424-9300 (CHEMTREC)
 727-535-1411

DATE: 2 JAN 09

=====

SECTION ONE - PRODUCT DESCRIPTION

=====

NAME: ULTRATEX SATIN FINISH SUPER HARD TEXTURE SYSTEM
CHEMICAL DESCRIPTION: Acrylic Latex Texture Satin
FORMULA: #2280

=====

SECTION TWO - HAZARDOUS INGREDIENTS

=====

CHEMICAL	%	CAS NO.	TLV	PEL	SARA 302	SARA 313	CERCLA RQ #	CARCINOGEN Y/N			NOTE
								NTP	IARC	OSHA	
Titanium Dioxide	8.76	13463-67-1	10 mg/m ³	10 mg/m ³	N	N	N	N	N	N	(1)
Aluminum Silicate	14.10	1332-58-7	10 mg/m ³	10 mg/m ³	N	N	N	N	N	N	(1)
Ethylene Glycol	1.68	107-21-1	50	100	N	Y	Y	N	N	N	(1)
Acrylic Resin	30.33	Proprietary	N/E	N/E							

=====

SECTION THREE - PHYSICAL DATA

=====

APPEARANCE: White **ODOR:** Nondescript, **BOILING POINT:** 100°C/212°F,
VAPOR PRESSURE: (mm of Hg.) : 17@20°C/68°F, **VAPOR DENSITY (Air = 1):** >1,
SPECIFIC GRAVITY (Water = 1): 1.23, **VOLATILE BY WEIGHT:** 42.2%
SOLUBILITY IN WATER: Dilutable, **EVAPORATION RATE (Water = 1) :** >1

=====

SECTION FOUR - FIRE AND EXPLOSION DATA

=====

FLASH POINT (°F / °C) [Closed Cup] : Non Combustible
FLAMMABLE LIMIT: - LEL N/A - UEL N/A
EXTINGUISHER MEDIA: N/A
SPECIAL FIRE FIGHTING PROCEDURES: N/A
UNUSUAL FIRE AND EXPLOSION HAZARDS: Polymer film will burn. Material can splatter above 100°C/212°F.

=====

SECTION FIVE - HEALTH HAZARD DATA

=====

THRESHOLD LIMIT VALUE: See section two

EFFECTS OF OVEREXPOSURE:

- Inhalation:** Vapor or mist can cause headache, nausea, irritation to the nose, throat and lungs.
- Skin Contact:** Irritating upon repeated and prolonged contact.
- Eye Contact:** Slightly irritating.

EMERGENCY & FIRST AID PROCEDURES:

- Inhalation:** Move subject to fresh air.
- Eye/skin Contact:** Flush eyes with large amounts of water for at least 15 minutes - see a physician if irritation persists. Wash Affected skin area with soap and water.

