



ANVIL PAINTS & COATINGS, INC.
1255 STARKEY ROAD
LARGO, FL 33771

MATERIAL SAFETY DATA SHEET

EMERGENCY TELEPHONE NUMBERS: 800-424-9300 (CHEMTREC)
 727-535-1411

REVIEW/UPDATE: 2 JAN 09 BY: _____

=====

SECTION ONE - PRODUCT DESCRIPTION

=====

NAME: CHALKY SURFACE CONDITIONER - PIGMENTED
CHEMICAL DESCRIPTION: Acrylic Latex Coating
FORMULA: #231

=====

SECTION TWO - HAZARDOUS INGREDIENTS

=====

CHEMICAL	%	CAS NO.	TLV	PEL	SARA 302	SARA 313	CERCLA RQ #	CARCINOGEN Y/N			NOTE
								NTP	IARC	OSHA	
Titanium Oxide	7.6%	13463-67-7	10mg/m3	10mg/m3	N	N	N	N	N	N	(1)
Glycol Ether EB	2.9%	111-76-2	25ppm	25ppm	N	Y	N	N	N	N	(1)
Acralate Polymer	17.2%	Supp. Conf.	N/E	N/E	N	N	N	N	N	N	(1)

=====

SECTION THREE - PHYSICAL DATA

=====

APPEARANCE: White **ODOR:** Nondescript, **BOILING POINT:** 100°C/212F°,
VAPOR PRESSURE: (mm of Hg.) : 17@20°C/68°F, **VAPOR DENSITY (Air = 1):** >1,
SPECIFIC GRAVITY (Water = 1): 1.08, **VOLATILE BY WEIGHT:** 73.3%
SOLUBILITY IN WATER: Dilutable, **EVAPORATION RATE (Water = 1):** >1

=====

SECTION FOUR - FIRE AND EXPLOSION DATA

=====

FLASH POINT (°F / °C) [Closed Cup]: Non Combustible
FLAMMABLE LIMIT: - LEL N/A
 - UEL N/A
EXTINGUISHER MEDIA: N/A
SPECIAL FIRE FIGHTING PROCEDURES: N/A
UNUSUAL FIRE AND EXPLOSION HAZARDS: Polymer film will burn. Material can splatter above 100°C/212°F.

=====

SECTION FIVE - HEALTH HAZARD DATA

=====

THRESHOLD LIMIT VALUE: See section two
EFFECTS OF OVEREXPOSURE:
Inhalation: Vapor or mist can cause headache, nausea, irritation to the nose, throat and lungs.
Skin Contact: Irritating upon repeated and prolonged contact.
Eye Contact: Slightly irritating.
EMERGENCY & FIRST AID PROCEDURES:
Inhalation: Move subject to fresh air.
Eye/skin Contact: Flush eyes with large amounts of water for at least 15 minutes - see a physician if irritation persists. Wash Affected skin area with soap and water.

