



ANVIL PAINTS & COATINGS, INC.
1255 STARKEY ROAD
LARGO, FL 33771

MATERIAL SAFETY DATA SHEET

EMERGENCY TELEPHONE NUMBERS:

800-424-9300 (CHEMTREC)
 727-535-1411

REVIEW/UPDATE: JAN 2009

=====

SECTION ONE - PRODUCT DESCRIPTION

=====

NAME: SATIN FINISH - ACRYLIC LATEX PAINT
CHEMICAL DESCRIPTION: Pigmented Vinyl Acrylic Latex Paint
FORMULA: #500 Series Builders Spec

=====

SECTION TWO - HAZARDOUS INGREDIENTS

=====

CHEMICAL	%	CAS NO.	TLV	PEL	SARA 302	SARA 313	CERCLA RQ #	CARCINOGEN Y/N			NOTE
								NTP	IARC	OSHA	
Propylene Glycol	4.7%	57-55-6	N/E	N/E	N	N	N	N	N	N	(1)
Hydrous Aluminum Silicate	5.0 - 15.0%	1332-58-7	10mg/m3	10mg/m3	N	N	N	N	N	N	(1)
Titanium Oxide	5.0 - 21.0%	13463-67-7	10mg/m3	10mg/m3	N	N	N	N	N	N	(1)

=====

SECTION THREE - PHYSICAL DATA

=====

APPEARANCE: White **ODOR:** Nondescript, **BOILING POINT:** 100°C/212°F,
VAPOR PRESSURE: (mm of Hg.) : 17@20°C/68°F, **VAPOR DENSITY (Air = 1):** >1,
SPECIFIC GRAVITY (Water = 1): 1.28, **VOLATILE BY WEIGHT:** 49.6%
SOLUBILITY IN WATER: Dilutable, **EVAPORATION RATE (Water = 1):** >1

=====

SECTION FOUR - FIRE AND EXPLOSION DATA

=====

FLASH POINT (°F / °C) [Closed Cup]: Non Combustible
FLAMMABLE LIMIT: - LEL N/A - UEL N/A
EXTINGUISHER MEDIA: N/A
SPECIAL FIRE FIGHTING PROCEDURES: N/A
UNUSUAL FIRE AND EXPLOSION HAZARDS: Polymer film will burn. Material can splatter above 100°C/212°F.

=====

SECTION FIVE - HEALTH HAZARD DATA

=====

THRESHOLD LIMIT VALUE: See section two
EFFECTS OF OVEREXPOSURE:

- Inhalation:** Vapor or mist can cause headache, nausea, irritation to the nose, throat and lungs.
- Skin Contact:** Irritating upon repeated and prolonged contact.
- Eye Contact:** Slightly irritating.

EMERGENCY & FIRST AID PROCEDURES:

- Inhalation:** Move subject to fresh air.
- Eye/skin Contact:** Flush eyes with large amounts of water for at least 15 minutes - see a physician if irritation persists. Wash Affected skin area with soap and water.

